



DSX Access Systems, Inc.

DSX-IP-HUB

DSX-IP-HUB Communications Interface

The DSX-IP-HUB is a module that connects to the Master Controller and to the Network which allows Sub Controller Communication to be routed via IP through the network to standard DSX-LAN modules connected to Sub Controllers or clusters of Sub Controllers.

The DSX-IP-HUB allows Controller Communication to be IP via the LAN without the use of PC Master Software. In fact, the IP-HUB can be used in some cases to replace PC Master software by adding or reconfiguring an existing panel to be a Master Controller and attaching a DSX-IP-HUB to it. The Sub Controllers use standard DSX-LAN modules and would only require minor reprogramming to allow communication with the new Master Controller through the IP-HUB.



- ❖ Web Interface
- ❖ Admin and User Passwords
- ❖ User Defined Password Complexity
- ❖ Powered from 12VDC via DSX Controller or 1040-CDM
- ❖ Used with a Master Controller takes the place of PC Master
- ❖ Configured with standard browser
- ❖ Transmitted Security Log with supervising HeartBeat
- ❖ VLAN capable
- ❖ RS-232/485 Panel Communications
- ❖ AutoSensing 10/100 - Gigabit Switch Compatible
- ❖ UDP Protocol with definable Sockets
- ❖ Default IP Address for programming

Specifications

Power

The DSX-IP-HUB is powered from a DSX Intelligent Controller's 12V fused output. It can also be powered from the DSX-1040CDM 12V outputs.

Mounting

The DSX-IP-HUB is designed to fit in the same Equipment Cabinet as the DSX-1048 and DSX-1022 Controllers. It can mount on the inside or rest in the bottom of the enclosure. It has three mounting holes and removable terminal blocks.

Communications

The DSX-IP-HUB module routes UDP controller traffic to specified IP Addresses. User selectable ports in the range of 4000 to 5000.

The Module will auto negotiate a 100MB connection when connected to a gigabit switch.

Size

4.75" H x 2.8" W x 1.5" D

Weight

7.5 oz.

Temperature/Humidity

Operating 0 to 70 C

Power Requirements

DC Input Voltage 5-14VDC @ 350ma

Warranty

Limited 2 Years

Example of Device Address (Routing) Table below in IP-HUB that allows the application drawing to the right to be possible. It shows some devices to be hardwired and then two standard LAN modules each connected to clusters of Sub controllers.

Select	IP Address	Devices
<input type="checkbox"/>	182.26.17.193	12,14,16,18,20,22
<input type="checkbox"/>	182.26.17.194	24,26,28,30,32,34
<input type="checkbox"/>	IPv4, IPv6 or DNS lookup	xx,xx

DeleteRow(s) Add Submit

